

Buccaneer Excavator Mini

This lightweight hydraulic mulcher is suitable for use with smaller excavators ranging from 1.5 to 30 tonnes and will cut branches up to 120mm in diameter.

The Buccaneer Excavator Mini is available in 5 different working widths. Available as **MDH** (Swing hammers) and **MDHF** (Fixed hammers).

Key Features

- Working with oil pressure ranges of 180 to 200 BAR
- Working with oil flows between 45 to 110 L/min
- Weight options from 310kg up to 640kg
- Skids to protect head
- Adjustable working height



Want to know more about the Buccaneer Excavator Mini?

Scan the QR code to the left with a smart phone or tablet and compatible app to instantly view the page.

Alternatively visit: <http://www.bomford-turner.com/forestry/buccaneer-excavator-mini/>



Product Specification

Micro Range	800	1000	1200	1400
Working Width	800mm / 2'6"	1000mm / 3'3"	1200mm / 3'9"	1400mm / 4'6"
Cutting Diameter (branches) up to	30mm / 1 1/4"	30mm / 1 1/4"	30mm / 1 1/4"	30mm / 1 1/4"
Weight	152kg / 335lbs	180kg / 396lbs	208kg / 458lbs	240kg / 529lbs
Oil Flow L/min	30-35L / 8-9 USG	30-40L / 8-10.5 USG	35-45L / 9-12 USG	40-50L / 10.5-13 USG
Oil Pressure	150-180	150-180	150-180	150-180

MDH Range	800	1000	1200	1400	1600
Working Width	800mm / 2'7"	1000mm / 3'3"	1200mm / 3'11"	1400mm / 4'7"	1600mm / 5'3"
Cutting Diameter (branches) up to	60mm / 2.36"	60mm / 2.36"	60mm / 2.36"	60mm / 2.36"	60mm / 2.36"
Weight	310kg / 683lbs	350kg / 771lbs	405kg / 892lbs	430kg / 948lbs	498kg / 1098lbs
Oil Flow L/min	45-55L / 12-15USG	60-65L / 16-17USG	60-65L / 16-17USG	70-80L / 18-21USG	70-80L / 18-21USG
Oil Pressure	180-200	180-200	180-200	180-200	180-200

MDHF Range	800	1000	1200	1400	1600
Working Width	800mm / 2'7"	1000mm / 3'3"	1200mm / 3'11"	1400mm / 4'7"	1600mm / 5'3"
Cutting Diameter (branches) up to	120mm / 4.72"	120mm / 4.72"	120mm / 4.72"	120mm / 4.72"	120mm / 4.72"
Weight	480kg / 1058lbs	545kg / 1202lbs	595kg / 1312lbs	620kg / 1367lbs	640kg / 1411lbs
Oil Flow L/min	45-85L / 12-22USG	60-95L / 16-25USG	60-95L / 16-25USG	70-100L / 18-26USG	70-110L / 18-29USG
Oil Pressure	180-200	180-200	180-200	180-200	180-200