



fleet.5



48 VOLT WITH DC SYSTEM
6 X 8V LEAD-ACID BATTERIES
18*8,5-8 STEEL RIMS
FRONT & REAR LIGHTS
MECHANICAL BRAKES ON
REAR WHEELS

ITALCAR INDUSTRIAL SRL | Via Bruino, 36 | 10040 Rivalta di Torino (TO)
Tel. +39 011 9040225 | Fax +39 011 9032986 | info@italcar.com | www.italcar.com



ITALCAR an Italian Brand



clicka mi piace - like us on



segui su - follow us on



fleet.5

places:	2
batteries:	6 x 8V, US8VGC standard
motor:	DC 48V – ADC
controller:	curtis 1266A – DC – 275A
transmission:	rear axle, 19 spline, ratio 12,31:1
steering:	self compensating single reduction rack and pignon
performances:	
suggested max speed	22 km/h
range	36 holes
max hill climbing ability	20%
dimensions:	
overall	2400mm x 1200mm x 1800mm
ground clearance (empty):	210mm
turning radius (min):	2,9 mt
wheel base	1650mm
chassis:	galvanized steel frame and powder coated
body:	PP impregnated and painted
suspensions:	
front	Independent suspensions
rear	leaf springs with hydraulic shock absorbers
brakes:	
rear	Mechanical brakes on rear wheel drum
tyres:	18 x 8,5 – 8 with steel rims
recommended pressure:	1,7 bar (25psi)
battery charger:	included with the vehicle - 48v, 220/230V
basic configuration:	Includes: reverse buzzer, front and rear lights, horn, direction indicators, rear-view mirrors, one piece plexiglass

All above specification were correct at the time of the printing and are considered indicatives and not binding. ITALCAR INDUSTRIAL S.r.l. maintains the right to bring any changes without notice

